

FUTURE ORIENTED WELL THOUGHT OUT
NEEDS ORIENTED
INTELLIGENT

Innovation@charge

Castellan AG



E-Powerload – charging system for electro mobility.

Castellan technology & design





CHARGING STATION 1

Customer requirements

With the Custom charging station, you have the opportunity to perfectly stage the tailor made charging station.

Charging station

- > 2 space charging station with 2 connection options each according to plug-in connections for 230 V and/or 400 V / 16 A / 32 A
- > Use as individual charging station or integrated into one of the accounting systems

Technik

- > Charging station for 2x 400 V / 32 A / 16 A
- > With 2x Schuko® connector per charging station (230 V)
- > Phase monitoring, wiring protection & Fault current circuit breaker
- > Internal electricity meter per charging station
- > Ethernet interface for future networks
- > USB interface
- > Real time clock
- > Illuminated gun holders
- > Wireless connection WLAN/UMTS (optional)

Casing

- > Aluminium 3 mm, powder coated according to RAL
- > For internal and external use, according to protection category IP54
- > Electronic component according to protection category IP67
- > Mechanical lock (locking system optional)
- > Robust design, secured against vandalism
- > Display or optional monitor
- > External dimensions: 500 mm (W) x 1,200 mm (H) x 350 mm (D)
- > Fastening via ground anchor, weight 69 kg

Billing types

Choose from our various billing methods and configure the technology according to your needs: SMS, bar code & 2D bar code, RFID 1, RFID 2, RFID 3, car park 1, car park 2

Design module

- A > Type 1 left/right
- B > Type 2 left/right
- C > Type 1 and Type 2
- D > Plug socket without cable



LADESTATION 2

Customer requirements

Choose your desired colours, logos and design.
Configure the technology according to your needs.

Charging station

- > 1 space charging station with 1 connection option each according to plug-in connections for 230V and/or 400V / 16 A / 32 A
- > Use as individual charging station or integrated into the billing system

Technology

- > Charging system for 230V and 400V / 32 A / 16 A
- > With Schuko® connector per charging station (230V)
- > Phase monitoring, wiring protection & Fault current circuit breaker
- > Internal electricity meter per charging station
- > Ethernet interface for future networks
- > USB interface
- > Real time clock
- > Illuminated gun holders
- > Wireless connection WLAN/UMTS (optional)

Casing

- > Aluminium 3 mm, powder coated according to RAL
- > For internal and external use, according to protection category IP54
- > Electronic component according to protection
- > Mechanical lock (locking system optional)
- > Robust design, secured against vandalism
- > Display or optional monitor
- > External dimensions: 340 mm (W) x 2,300 mm (H) x 450 mm (D)
- > Fastening via ground anchor, weight 89 kg

Billing types

Choose from our various billing methods and configure the technology according to your needs: SMS, bar code & 2D bar code, RFID 1, RFID 2, RFID 3, car park 1, car park 2

Design module

- A > Type 1
- B > Type 2



CHARGING STATION 3



Customer requirements

Wählen Sie Ihre Wunschfarben, Logos und Design.
Konfigurieren Sie sich die Technik nach Ihren Bedürfnissen.

Charging station

- > 2 space charging station with 2 connection options each according to plug connections for 230V and/or 400V / 16 A / 32 A
- > Benutzung als Einzella-destination oder eingebunden in eines der Abrechnungssysteme

Technology

- > Charging station for 1x 230V and 1x 400V / 32 A / 16 A
- > With 2x Schuko® connectors per charging station (230V)
- > Phase monitoring, wiring protection & Fault current circuit breaker
- > Internal electricity meter per charging station
- > Ethernet interface for future networks
- > USB interface
- > Real time clock
- > Illuminated gun holders
- > Wireless connection WLAN/UMTS (optional)

Casing

- > Aluminium, 3 mm powder coated according to RAL
- > For internal and external use, according to protection category IP54
- > Electronic component according to protection category IP67
- > Mechanical lock (locking system optional)
- > Robust design, secured against vandalism
- > Display or optional monitor
- > External dimensions: 340 mm (W) x 2,300 mm (H) x 450 mm (D)
- > Fastening via ground anchor, weight 89 kg

Billing types

Choose from our various billing methods and configure the technology according to your needs: SMS, bar code & 2D bar code, RFID 1, RFID 2, RFID 3, car park 1, car park 2

Optional functions

- > Hands free system with call buttons
- > Remote control system with remote switchable fault current circuit breakers
- > Voice prompt for accessible use
- > Activation by code keyboard
- > Activation by RFID card
- > Activation by magnetic card
- > Activation by bar code and 2D bar code
- > Built in camera for video surveillance of the car park
- > Operation via network system: Technical requirements can be switched on for external cost calculation system, Network and computer with own IP

Design module

- A > Type 1 left/right
- B > Type 2 left/right
- C > Type 1 and Type 2



RECEPTION CHARGING STATION



Visitor reception

“First impressions count”, as the saying goes. With this reception station, you can show every visitor how progressive and customer oriented your company is. Your business card Future, a clear sign in front of your building and a statement. Orientation and greeting in your design.

Charging station

- > 2 space charging station with 2 connection options each according to plug connections for 230V and/or 400V / 16 A / 32 A
- > Use as individual charging station or integrated into the billing system

Technology

- > Charging station for 1x 230V and 1x 400V / 32 A / 16 A
- > With 2x Schuko® connectors per charging station (230V)
- > Phase monitoring, wiring protection & Fault current circuit breaker
- > Internal electricity meter per charging station
- > Ethernet interface for future networks
- > USB interface
- > Real time clock
- > Illuminated gun holders
- > Wireless connection WLAN/UMTS (optional)

Casing

- > Aluminium 3 mm, powder coated according to RAL
- > For internal and external use, according to protection category IP54
- > Electronic component according to protection category IP67
- > Mechanical lock (locking system optional)
- > Robust design, secured against vandalism
- > External dimensions: 440 mm (W) x 2,100 mm (H) x 350 mm (D)
- > Fastening via ground anchor, weight 99 kg

Billing by SMS

Using our own billing system, you can control the activation and billing of your charging pole, free of charge.

Car park lighting

The LED lighting creates a pleasant illumination of the car park. The visitor feels welcome straight away, and can organise their lift via the call function.

Billing types

Choose from our various billing methods and configure the technology according to your needs: SMS, bar code & 2D bar code, RFID 1, RFID 2, RFID 3, car park 1, car park 2

Design module

- A > Type 1 left/right
- B > Type 2 left/right
- C > Type 1 und Type 2
- D > Plug socket without cable



WALL CHARGING STATION



Technology

- > Charging system for 230V and 400V / 32 A / 16 A
- > With Schuko® connector per charging station (230V)
- > Phase monitoring, wiring protection & Fault current circuit breaker
- > Internal electricity meter per charging station
- > Ethernet interface for future networks
- > USB interface
- > Real time clock
- > Illuminated gun holders
- > Wireless connection WLAN/UMTS (optional)

Casing

- > Aluminium 3 mm, powder coated according to RAL
- > For internal and external use, according to protection category IP54
- > Electronic component according to protection category IP67
- > Mechanical lock (locking system optional)
- > Robust design, secured against vandalism
- > Display or optional monitor
- > Dimensions: 600 mm (B) with side gun holders
600 mm (W) x 600 mm (H) x 250 mm (D)
- > Fastening directly onto concrete wall via distance bushings

Billing types

Choose from our various billing methods and configure the technology according to your needs: SMS, bar code & 2D bar code, RFID 1, RFID 2, RFID 3, car park 1, car park 2

Optional functions

- > Gas measurement sensors for car park surveillance
- > Sensors to monitor the car park for radio controlled display
- > Radio controlled display Indoor
- > Radio controlled display Outdoor
- > Hands free system with call buttons and room wiretapping function
- > Remote control system with remote switchable fault current circuit breakers
- > Voice prompt for accessible use
- > Activation by code keyboard
- > Activation by RFID card
- > Activation by magnetic card
- > Activation by bar code and 2D bar code
- > Built in camera for video surveillance of the car park
- > Operation via network system: Technical requirements can be switched on for external cost calculation system, Network and computer with own IP

Customer requirements

Choose your desired colours, logos and design.
Configure the technology according to your needs.

Wall charging station

- > 2 space charging station with 2 connection options each according to plug connections for 230V and/or 400V / 16 A / 32 A
- > Use as individual charging station or integrated into the billing system

Design module

- A > Type 1 left/right
- B > Type 2 left/right
- C > Type 1 and Type 2
- D > Plug socket without cable



NEEDS ASSESSMENT

Extras

Spiral cable

Plug type 1	<input type="checkbox"/>	Left	<input type="checkbox"/>	Right
Plug type 2	<input type="checkbox"/>	Left	<input type="checkbox"/>	Right

Casing sockets

CEE	<input type="checkbox"/>	Left	<input type="checkbox"/>	Right
Schuko®	<input type="checkbox"/>	Left	<input type="checkbox"/>	Right

Current strength

400 V/16 A	<input type="checkbox"/>
400 V/32 A	<input type="checkbox"/>

Display

12" Monitor	<input type="checkbox"/>
-------------	--------------------------

Options

Gas measurement sensors for car park surveillance	<input type="checkbox"/>
Sensors to monitor the car park for radio controlled display	<input type="checkbox"/>
Radio controlled display Indoor	<input type="checkbox"/>
Radio controlled display Outdoor	<input type="checkbox"/>
Hands free system with call button and room wiretapping function - GSM	<input type="checkbox"/>
Hands free system with call button and room wiretapping function - analogue	<input type="checkbox"/>
Remote control system with remote switchable fault current circuit breakers	<input type="checkbox"/>
Internal electricity meter	<input type="checkbox"/>
Built in camera for video surveillance of the car park	<input type="checkbox"/>

Reading device

RFID	<input type="checkbox"/>
Bar code	<input type="checkbox"/>
Magnetic card reader	<input type="checkbox"/>
Code - keyboard	<input type="checkbox"/>

RFID - chip cards

Piece

Connection to a web portal

Ethernet interface	<input type="checkbox"/>
Wireless	<input type="checkbox"/>
WLAN	<input type="checkbox"/>
UMTS	<input type="checkbox"/>

Assembly

Wall	<input type="checkbox"/>
Pole/ support	<input type="checkbox"/>

Billing with a car park ticket machine

RFID	<input type="checkbox"/>
Bar code	<input type="checkbox"/>
Magnetic card reader	<input type="checkbox"/>
Code keyboard	<input type="checkbox"/>



Castellan AG
Landstraße 20
57223 Kreuztal, Germany

Telephone: +49 2732 55307-0
Fax: +49 2732 55307-22

info@castellan-ag.com
www.castellan-ag.com

